PATENT

Attorney Docket No. 65857-0094 Serial No. 10/029,853

## Amendments to the Claims

1. (Currently Amended) A hose for transmitting liquids, the hose comprising:

an inner tubular portion made of a chlorinated polyethylene polymer, <u>said</u> chlorinated polyethylene polymer having a percentage, by weight, less than thirty percent of the material composition of said inner tubular portion and which has been peroxide cured;

- a ply of metal wire braided directly over the inner tubular portion;
- a thin rubber layer covering the wire;
- a layer of polyester yarn braided over the thin rubber layer, and
- a dye containing urethane deposited over and into the layer of yarn.
- 2. (Original) The hose of claim 1 wherein the formulation of the tubular portion includes a plasticizer including a blend of polymeric and ester based components.
- 3. (Currently Amended) The hose of claim [[2]] 1 wherein the formulation of the tubular portion includes a heat stabilizer including a blend of metal oxides and silicates.
- 4. (Currently Amended) The hose of claim [[3]] 1 wherein the formulation of the tubular portion includes a vulcanizing agents in the form of peroxide and cross-linking agents which effect the peroxide cure.
  - 5. (Canceled)
- 6. (Currently Amended) The hose of claim 1 wherein the formulation of the tubular portion includes a vulcanizing agents in the form of peroxide and cross-linking agents which effect the peroxide cure.
- 7. (Original) The hose of claim 1 wherein the thin rubber layer is comprised of the same formulation as the tubular portion.



Attorney Docket No. 65857-0094 Serial No. 10/029,853

vulcanizing the hose.

PATENT

- 8. (Original) The hose of claim 7 wherein the ply of metal wire is comprised of stainless steel or brass coated steel wire.
- 9. (Original) The hose of claim 1 wherein the ply of metal wire is comprised of stainless steel or brass coated steel wire.
- 10. (Currently Amended) A tube comprising a wall made of chlorinated polyethylene polymer formulation which has been peroxide cured and includes a plasticizer comprising a blend of polymeric and enter ester based components and a dye containing urethane deposited over said wall.
- 11. (Original) The tube of claim 11 wherein the formulation includes a heat stabilizer including a blend of metal oxides and silicates.
- 12. (Original) The tube of claim 11 wherein the formulation includes vulcanizing agents in the form of peroxide and cross-linking agents which effects the peroxide cure.
- 13. (Currently Amended) The tube of claim 12 wherein the formulation includes quinoline-type antegradants antidegradants.
- 14. (Withdrawn) A method of making a hose for transmitting liquids, comprising: forming an inner tubular portion made of a chlorinated polyethylene polymer formulation which has a peroxide component;

braiding a ply of metal wire directly over the inner tubular portion; covering the wire with a thin rubber layer; braiding a layer of polyester yarn over the thin rubber layer; depositing a dye containing urethane over the layer of yarn, and

15. (Withdrawn) The method of claim 14 wherein the formulation of the tubular portion includes a plasticizer including a blend of polymeric and ester based components.



Attorney Docket No. 65857-0094 Serial No. 10/029,853 **PATENT** 

- 16. (Withdrawn) The method of claim 15 wherein the formulation includes a heat stabilizer including a blend of metal oxides and silicates.
- 17. (Withdrawn) The method of claim 16 wherein the formulation includes vulcanizing agents in the form of peroxide and cross-linking agents which effect the peroxide cure.
- 18. (Withdrawn) The method of claim 4 wherein the formulation includes quinoline-type antegradants.
- 19. (Withdrawn) The method of claim 18 wherein the formulation includes carbon black and low molecular weight waxes.

